

NANO 30CS

LOW-LEVEL ACCESS



STANDARD SPECIFICATIONS

Performance

Maximum working height	4.95 m
Maximum platform height	2.95 m
Closed platform height	0.83 m
Working outreach	0.65 m
Platform dimensions L x W	0.55 m x 0.55 m
Working foot print	1.20 m x 0.76 m
Safe working load - platform	200 kg (1 person + tools)
Safe working load - standard tray	20 kg
Maximum manual force	200 N
Maximum gradient for operation	0,5°
Maximum wind force	0 m/s (Indoors Use Only)
Maximum weight, including payload	533 kg
Maximum castor point load	182 kg (1.78 kN)
Maximum Wheel force	182 kg (1.78 kN)
Sound Pressure Level	Less than 76 dBA
Vibration Level	Less than 0.5 m/s ²

Closed dimensions

Length	1.20 m
Width	0.76 m
Height	1.94 m
Weight	333 kg

Battery charger specification

Input Voltage	90-265V AC
Frequency	50-60 Hz
Output	12V DC, 6A

STANDARD FEATURES

- Access steps with handrails
- Footprint (1.20 m x 0.76 m)
- Optimal width to fit through single doorways
- Self locking fixed wheels when raised
- Small platform (0.55 x 0.55 m)
- Simple push button controls from platform
- Quality steel construction and dual mast with ultra glide technology
- Durable powder coated finish
- Fail safe hydraulic circuit
- Emergency lower from ground level
- Hydraulic circuit with non-return valve
- Acoustic signal when lifting and lowering
- Spirit Level
- Battery charge indicator
- Lanyard attachment
- Forklift pockets
- Anti-climb basket with removable gates for emergency access

ACCESSORIES & OPTIONS

- Plug - 230V 2P EURO
- Plug - 110V 3P UK
- Plug - 230V 3P UK
- Plug - US STYLE for Latin America
- Tool tray
- Tool Tethering options

KEY SPECIFICATIONS

Platform carrying capacity: 200 kg
Dimension: 1.20 m x 0.76 m

Working Height: 4.95 m
Total Weight: 333 kg

KEY FEATURES

- 4.95 m working height
- Access step for entry into platform
- Only 1.20 m x 0.76 m working footprint
- Passes easily through single doorways
- Small 0.55 m x 0.55 m platform allows access into confined spaces
- Heavy duty Auto-Lok wheels on elevation

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel.: +31 (0)23 565 5665
www.jlg.com

An Oshkosh Corporation Company

23.07.2025