

POWER TOWER CS

LOW-LEVEL ACCESS



KEY SPECIFICATIONS

Platform carrying capacity:

250 kg

Dimension:

1.62 m x 0.78 m

Working Height:

5.00 m

Total Weight:

341 kg

KEY FEATURES

- 3.00 m platform height, 5.00 m working height
- 250 kg safe working load (1 person)
- Compact - only 0.78 m wide, passes easily through standard doorways
- Small 0.55 m x 0.55 m platform allows access into confined spaces
- Only 1.62 m x 0.78 m working footprint
- Saloon gates for easy access

STANDARD SPECIFICATIONS

Performance

Maximum working height	5.00 m
Maximum platform height	3.00 m
Closed platform height	0.74 m
Working outreach	0.65 m
Platform dimensions L x W	0.55 m x 0.55 m
Working foot print	1.62 m x 0.78 m
Safe working load	250 kg
Maximum manual force	200 N
Maximum gradient for operation	0.5°
Maximum wind force	Internal use only 0 m/s
Maximum castor point load	215 kg (2.11 kN)
Maximum wheel force	215 kg (2.11 kN)
Power Sound Level	Less than 70 dBA

Closed dimensions

Length	1.62 m
Width	0.78 m
Height	1.85 m
Weight	341 kg

Power options

Battery	12 V c/w automatic charger
Mains	110 V or 230 V
Controls	Simple push button basket controls
Construction	Heavy duty fabricated steel superstructure, bushed pivots, tough powder coated finish
Safety	CE marked, complies with applicable European legislation including the Machinery Directive using the EN280 design standard. Full fail-safe hydraulics, automatic locking wheels

STANDARD FEATURES

- Footprint (1.62 m x 0.78 m)
- Optimal width to fit through single doorways
- Small platform (0.55 m x 0.55 m)
- Simple push button controls from platform
- Quality steel construction
- Durable powder coated finish
- Fail safe hydraulic circuit, with non-return valve
- Emergency lower from ground level
- Acoustic signal when lifting and lowering
- Spirit Level
- Battery charge indicator

ACCESSORIES & OPTIONS

- Tool Tethering
- Plug - 230V 2P EURO
- Plug - 230V 3P UK
- Plug - US STYLE for latin america
- Power to basket

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel.: +31 (0)23 565 5665
www.jlg.com

An Oshkosh Corporation Company